



MIDI Fuse Cold Resistance

Part #	Voltage Rating	Amp Rating	Cold Resistance (±20%)
ADS-C23	32V/48V/58V/72V	23A	2.25
ADS-C30	32V/48V/58V/72V	30A	2.03
ADS-C40	32V/48V/58V/72V	40A	1.55
ADS-C50	32V/48V/58V/72V	50A	1.25
ADS-C60	32V/48V/58V/72V	60A	1.1
ADS-C70	32V/48V/58V/72V	70A	0.95
ADS-C80	32V/48V/58V/72V	80A	0.9
ADS-C100	32V/48V/58V/72V	100A	0.7
ADS-C125	32V/48V/58V/72V	125A	0.5
ADS-C150	32V/48V/58V/72V	150A	0.4
ADS-C175	32V/48V/58V/72V	175A	0.3
ADS-C200	32V/48V/58V/72V	200A	0.2

MIDI Time Current Characteristics

% of Rating	Opening Time Min/Max (S)	
	23-125A	150-200A
75	-/-	360,000s/-
100	360,000 s/-	-/-
110	14.400 s/-	-/-
150	90s/3,600s	-/-
200	3s/100s	1s/15s
300	0.3s/3s	-/-
350	-/-	0.3s/5s
500	0.1s/1s	0.1s/1s

